## Business-Class Video Conferencing for the Small Meeting Room

### Lifesize<sup>®</sup> Icon Flex<sup>™</sup>

Forhandler: AV-Concept aps Tlf: 30321889 mail: info@av-concept.dk www.av-concept.dk

# It's Your Meeting—You Choose the Application

At Lifesize, we know there's a better way to have an exceptional meeting experience because we've spent over a decade perfecting it. Meet Lifesize lcon Flex—a complete, business-class video and audio conferencing solution ideally suited for small meeting rooms that gives businesses the power of choice. So whether your business is using Microsoft<sup>®</sup> Lync<sup>®</sup>, Google Hangouts<sup>™</sup>, Cisco Jabber<sup>®</sup>, Skype<sup>™</sup>, or our favorite, Lifesize<sup>®</sup> Cloud, all you have to do is bring your laptop to the meeting and connect it to Lifesize lcon Flex for a video collaboration experience like no other.

And what makes Lifesize Icon Flex stand out from the rest is that our elegantly designed Lifesize Phone can also be used as a stand-alone conference phone, giving your company one less device to manage in the meeting room.

Best of all, Lifesize stands by every solution we make with our world-class service and support team.

Your laptop. Your collaboration app. Lifesize Icon Flex. It's that simple.



## Your Meeting, Your Way

- Perfectly sized for small meeting rooms
- Designed for use with collaboration applications like Microsoft Lync, Google Hangouts, Cisco Jabber, Skype (or our favorite, Lifesize Cloud)
- Business-class, award-winning hardware provides an exceptional meeting experience
- Backed by our world-class customer service and support team that's always there when you need them

#### LIFESIZE CAMERA

- Provides superb, lifelike HD 1080p30/720p60 video
- Ultra-quiet pan/tilt with 6x zoom: 3x optical zoom and 2x digital zoom
- Low-dispersion, 8-element glass lens, with anti-glare coating and high clarity, molded aspherical glass
- Proprietary lens iris reduces optical diffraction
- Razor-sharp image quality provided by five-zone autofocus
- Increased durability and optimal heat distribution through machined aluminum body

#### LIFESIZE PHONE

- Elegantly designed touchscreen conference phone with 360° microphone coverage and powerful loudspeaker for maximum voice pickup and crystal-clear audio
- Can be used as a stand-alone audio conference phone by connecting to your IP-PBX

#### LIFESIZE REMOTE CONTROL

Controls camera (pan/tilt/zoom) and audio (mute/volume)



### Lifesize<sup>®</sup> Icon Flex<sup>™</sup>

## **Product Specifications**

#### SYSTEM COMPONENTS

Lifesize Icon Flex with embedded PTZ camera Lifesize Phone or Lifesize Digital MicPod Lifesize Remote Control Power supply and cable (2 m) USB A to USB B cable (5 m) HDMI cable (5 m) Ethernet cable (3 m) Ouick reference card

#### SYSTEM REQUIREMENTS

Windows 7 or higher Mac OS X 10.8 or higher USB 2.0 port

#### **DESIGNED FOR USE WITH:**

Microsoft Lync Google Hangouts Cisco Jabber Skype Lifesize Cloud Windows\* Mac\*

#### **TECHNICAL SPECIFICATIONS**

1080p30 6x PTZ camera

- Full HD 1920x1080p30/1280x720p60 resolution
- Progressive scanning
- 16:9 aspect ratio
- Wide-angle zoom lens with 70-degree field of view
- 245-degree pan, 72-degree tilt
- 3x optical lossless zoom
- 2x digital zoom
- Power LED

#### VIDEO OUTPUT (1)

1 x USB B (1080p30/720p60) to laptop Laptop can be connected to HD display separately

#### FULLY INTEGRATED, HD AUDIO LIFESIZE PHONE

90 Hz up to 22 kHz 32 kHz audio sampling Pickup range up to 4.57 m (15 ft) Powered by Lifesize Icon Flex through Lifesize Link cable Ships with 9 m Lifesize Link cable Optional 4 m or 15 m cable available

#### System Speaker

Powerful rare-earth magnet loudspeaker driver
 Large, acoustically suspended speaker enclosure

#### System Microphones

- Four low-noise microphones
- -80 dB SNR before noise reduction
- Sample rates: 32 kHz
  Beam-forming algorithm steers the microphones to the location of the talker for greater voice pickup and reduced room noise

Touchscreen Display – WQVGA capacitive multitouch display – 4.3 inch (diagonal)

#### FULLY INTEGRATED, HD AUDIO LIFESIZE DIGITAL MICPOD

90 Hz up to 22 kHz Sample rates: 32 kHz Pickup range up to 4.57 m (15 ft) Powered by Lifesize Icon Flex through Lifesize Link cable Ships with 4 m Lifesize Link cable Optional 9 m or 15 m cable available

#### System Microphones

- Three low-noise microphones
- 80 dB SNR before noise reduction



Performance dependent on collaboration application being used

HEADQUARTERS Austin, Texas, USA +1512 347 9300 Toll Free US +1 877 543 3749

**EMEA REGIONAL OFFICE** Munich, Germany +49 89 20 70 76 0 Toll Free Europe +00 8000 999 09 799 Forhandler: AV-Concept aps Tlf: 30321889 mail: info@av-concept.dk www.av-concept.dk

# lifesize

 $\circledcirc$  2015 Logitech. All rights reserved. Information contained in this document is subject to change without notice. Lifesize is the registered trademark or trademark of Logitech. All other trademarks are the property of their respective owners.

DS\_lcon Flex\_A4\_0115

#### **GENERAL AUDIO FEATURES**

Full duplex for natural conversations Echo cancellation for echo-free calls Automatic gain control Automatic noise reduction

#### AUDIO INPUT (1)

 $1\,\mathrm{x}\,\mathrm{Lifesize}\,\mathrm{Link}$  (Lifesize Phone/Digital MicPod) via USB cable to laptop

#### AUDIO OUTPUT (1)

1 x Lifesize Link (Lifesize Phone) via USB cable to laptop

#### **USER FEATURES**

Heads-up remote control Intelligent touchscreen interface with Lifesize Phone Manage camera pan, tilt, zoom, audio mute/unmute, volume up/down LEDs on phone or micpod for in-call (blue) and mute (red) indication

#### SECURITY

Kensington Security Slot

#### POWER

AC voltage 100–240V, 50–60 Hz, 2.31A via external 19VDC power supply

#### **ENVIRONMENTAL DATA**

Operating temperature: 0°C (32°F) to 40°C (104°F) Operating humidity: 15% to 85%, noncondensing Storage temperature: -20°C (-4°F) to 60°C (140°F) Storage humidity: 10% to 90%, noncondensing

#### DIMENSIONS

Width: 216.5 mm (8.52") Depth: 119.4 mm (4.70") Height: 125.4 mm (4.94") Weight: 1.04 kg (2.29 lbs)

#### **MOUNTING OPTIONS**

Mounting holes: 2 x M5 screw holes 150 mm (6 in) apart Mounting screws: 2 x M5 screws (Max insertion depth: 3.8 mm)

#### **REGULATORY NUMBER:**

LFZ-033

#### RUNS ON:



DESIGNED FOR USE WITH:

**D** 



