

Tlf: 30321889 – mail: info@av-concept.dk – www.av-concept.dk

N3981K N-Series Professional Displays







- Ideal solution for professional environments -Customise your content and display in portrait or landscape orientation across one or multiple displays
- Intuitive friendly software Built-in apps enable users to connect, present and collaborate globally, both in-person and remotely
- Built-in media player and scheduling functionality - Create, customise and schedule media playlists and display content at a specific date or time
- Optimised for conferencing solutions -Compatible with a variety of accessories such as web cameras, Bluetooth speakers, and motorised trollies



The N-Series Professional Displays are designed to enhance the current conferencing setups of corporate and education settings to accommodate hybrid work and distance-learning scenarios. Intuitive friendly software enables users to connect, present and collaborate globally, both in-person and remotely.

Featuring portrait and landscape orientation, the N-Series are built for usage in corporate lobbies and reception areas, conference rooms, lecture halls, digital signage and other professional environments.

Specifications

EAN: 5055387666887, Colour: Black	
Display	
Back light	Direct type LED
Size (diagonal)	98"
Resolution	3840x2160
Brightness	500
Contrast ratio	1,200:1
Contrast ratio (dynamic)	3,000:1
/iewing angle	178°
Response time	8ms
life	50,000 hours
Display colours	1,070
Speaker count	2
Vatts per speaker	10W
Surface hardness	ЗН
Glass	HAZE: 25%
Nir gap	4.00mm
Physical spec	
Dimensions (W x D x H) mm	2212 x 79.4 x 1268.4
Vall-hanging screw spec	M8*25mm
ESA holes	800*600
n the box	European Standard Power Cord
	American Standard Power Cord
	British Standard Power Cord
	HDMI Cable 3M
	Remote Control
	Battery
	QSG
onnections	Inputs 3 x HDMI 2.0, 1 x USB-C, 1 x USB 2.0, 1 x USB 3.0,
	1 x RS232, 2 x RJ45, 1 x OPS slot
	Outputs 1 x HDMI 2.0, 1 x S/PDIF, 1 x Audio 3.5mm
ezel size (top)	26.00mm
ezel size (bottom)	26.00mm
ezel size (left)	26.00mm
ezel size (right)	26.00mm
perating conditions	24/7
perating temperature (max)	40°C
4/7 operation	Yes
let weight	69.4 kg
ross weight	90.3 kg
Vireless - antenna	Optional Accessory
Vireless - technology	802.11ac/b/g/n/a/ax
/ireless - operating frequency	2.4Ghz/5Ghz
Power	
	100-240V~ 50/60Hz
ower supply	
ower consumption (standby)	0.5W
ower consumption (max)	515W
ower consumption - average	340
vatts)	
peration System	Android 11
ystem version	Android 11
PU	Quad A55
PU	Mali G51
	4GB
RAM Storage	32GB
	17 languages: Arabic, Czech, Danish, Dutch, English, French,
Storage	17 languages: Arabic, Czech, Danish, Dutch, English, French, German, Italian, Polish, Portuguese, Romanian, Russian,
Storage	17 languages: Arabic, Czech, Danish, Dutch, English, French, German, Italian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),
Storage	17 languages: Arabic, Czech, Danish, Dutch, English, French, German, Italian, Polish, Portuguese, Romanian, Russian,



AV-Concept ApS Professionelt AV-Udstyr

Tlf: 30321889 - mail: info@av-concept.dk - www.av-concept.dk

Copyright © 2023, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 03112023011955