

# DATA SHEET

## VIDI™ 250

### 4K CONFERENCING CAMERA



The Vidi™ 250 is a wide angle 4k camera designed for use with conferencing systems. Intended for huddle rooms or small to medium conferencing rooms, the Vidi 250 has a 120° field of view, allowing everyone in the room to be seen. The Vidi 250 uses auto framing technology to adjust the focus and zoom to keep participants in view. The Vidi 250 can be either display mounted or wall mounted.

#### FEATURES

- LED indications for camera activity
- Wide angle 120° Field of View
- Auto framing technology to keep participants in frame
- Electronic Pan/Tilt/Zoom with 5x zoom
- Multi-microphone array
- Display mount and wall mount options available
- Covered by Biamp Systems' three-year warranty

#### ARCHITECTS & ENGINEERS SPECIFICATION

The conferencing camera shall be designed to connect with soft codec conferencing systems. The conferencing camera shall be capable of transmitting video signals up to 2160p resolution at 30 frames per second. The conferencing camera shall have a 120° field-of-view. The conferencing camera shall be equipped with a 5x zoom and electronic pan, tilt, and zoom (ePTZ) capabilities. The conferencing camera shall include auto framing capabilities to automatically adjust the ePTZ to intelligently track users. The conferencing camera shall be mountable on a wall or display. The conferencing camera shall be CE marked and compliant with the RoHS directive. Warranty shall be three years. The conferencing camera shall be the Vidi™ 250.

## VIDI 250 SPECIFICATIONS

<b>CAMERA</b>		<b>Power Source</b>	
<b>Diagonal Field of View:</b>	120 Degrees	<b>USB-C:</b>	< 10W
<b>Image Sensor:</b>	12 Megapixel	<b>Overall Dimensions</b>	
<b>Focus Distance:</b>	100 cm	<b>Height:</b>	2.0 inches (50 mm)
<b>Digital Zoom:</b>	5x	<b>Width:</b>	2.0 inches (50 mm)
<b>Positioning:</b>	Autoframing capability	<b>Depth:</b>	2.8 inches (70 mm)
	Electronic Pan/Tilt/Zoom	<b>Weight:</b>	0.35 lbs (160 g)
	UVC controlled	<b>Environmental:</b>	
<b>Indicators:</b>	Camera Active Indicator (White/Off LED)	<b>Operating Temperature:</b>	32 - 104° F (0 - 40° C)
<b>Supported Video Resolutions:</b>	720p @ 30fps 1080p @ 30fps 2160p @ 30fps	<b>Relative Humidity:</b>	0 - 95% (non-condensing)
		<b>Altitude:</b>	0 - 10,000 ft (0 - 3000m) MSL
<b>Interfaces</b>		<b>Compliance:</b>	CE Marked (Europe) UKCA (Great Britain)
<b>USB 3.0:</b>	1x Type C		

## OPTIONAL ACCESSORIES



**VMA 200-DM**  
Side Display Mount



**VMA 200-WM**  
Wall Mount


**AV-Concept ApS**  
Professionelt AV-Udstyr

Tlf: 30321889 – mail: [info@av-concept.dk](mailto:info@av-concept.dk) – [www.av-concept.dk](http://www.av-concept.dk)

Biamp and Vidi are either trademarks or registered trademarks of Biamp Systems, LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.

**biamp.**

 [biampinfo@biamp.com](mailto:biampinfo@biamp.com)

 +1 503 641 7287

 [www.biamp.com](http://www.biamp.com)

VIDDS-1202-2208-EN-R1