

SPEECH-104D - Amplifier System

new



Professional lectern with integrated 2-channel multifrequency receiver unit with UHF PLL technology and class D amplifier

- Built-in class D mixing amplifier and speaker system, 80 W
- Operation via built-in rech. lead gel batteries: 2 x 12 V/7 Ah (operating time: up to 16 hours)
- Integrated battery charging, supplied with charger
- 2 x 16 selectable UHF frequencies (863.1-864.9MHz)
- 1 input via comb. jack mic (XLR)/line (6.3 mm jack)
- 1 stereo aux input via RCA jacks
- Each input with gain control
- 2 shock-absorbing XLR jacks on the top part of the lectern for 2 optional gooseneck microphones (use one microphone input each) or one microphone and one optional LED gooseneck light
- 12 V phantom power
- 1 stereo line output via RCA jacks
- NEUTRIK SPEAKON connection (8 Ohm) for external speaker
- 2-way speaker system
- High-quality wooden cabinet with replaceable black bottom plates
- Top part of the lectern with folding document compartment
- Delivery consists of 2 boxes

Supplied w/o gooseneck microphone and w/o gooseneck lamp. Matching microphone EMG-650P and matching LED gooseneck lamp GNL-304 are available at option.



AV-Concept
Professionelt AV-Udstyr

AV-Concept ApS
Glasmagervej 13, Fensmark
4684 Holmegaard
30 32 18 89
www.av-concept.dk

Matching microphone transmitters or pocket transmitters are available at option, e.g. TXA-800HSE, TXA-800HT.

Licence-free in the EU.

Technical data:

| | |
|---------------------------|---|
| Rated power (P_{RMS}) | : 80 W |
| Peak output power | : 120 W |
| Frequency range | : 70-20,000 Hz |
| Carrier frequency | : 863.1-864.9 MHz |
| Operating range | : ? 25 m |
| Inputs | : 2 mV (mic 1), 13 mV (line), 20 mV (mic 2-3), 100 mV (aux) |
| Link | : - |
| THD | : - |
| Max. SPL | : - |
| Equalizer, bass | : - |
| Equalizer, midrange | : - |
| Equalizer, treble | : - |
| Power supply | : rech. batt. 2 x 12 V/7 Ah, DC 12 V/1.5 A via suppl. charger |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : 525 x 1,120 x 440 mm |
| Weight | : 30 kg |
| Connections | : 1 x XLR (mic 1) 1 x 6.3 mm jack (line), 2 x XLR (mic 2-3), 1 x RCA L/R (aux), 1 x RCA L/R (line out), 1 x |